



CASE IH LOADERS

TRACTOR/LOADER COMPATIBILITY

TRACTOR	LOADER	MAX. LIFT CAPACITY 31.5 in. (800 mm) Forward of Pivot Pin LBS. (KG) – NSL / MSL	MAX. HEIGHT Under Level Bucket IN. (MM) – NSL/MSL	BREAKOUT FORCE 31.5 in. (800 mm) Forward of Pivot Pin LBS. (KG) – NSL/MSL
FARMALL® COMPACT A SERIES				
FARMALL 35A FARMALL 40A	L340A	890 (404) [†]	98 (2 500)	1,900 (862) [†]
FARMALL COMPACT C SERIES				
FARMALL 35C FARMALL 40C	L350A	1,540 (699) [†]	105 (2 667)	2,640 (1 197) [†]
FARMALL 45C FARMALL 55C	L360A	1,830 (830) [†]	112 (2 852)	3,114 (1 412) [†]
FARMALL 45C CVT FARMALL 55C CVT	L350A	1,540 (699) [†]	105 (2 667)	2,640 (1 197) [†]
FARMALL UTILITY A SERIES				
FARMALL 50A FARMALL 60A FARMALL 70A	L545 L555	1,742 (790) / 2,205 (1 000) 1,940 (880) / 2,734 (1 240)	102 (2 590) / 106 (2 680) 105 (2 670) / 105 (2 670)	2,998 (1 360) / 3,131 (1 420) 3,241 (1 470) / 3,527 (1 600)
FARMALL 55A FARMALL 65A FARMALL 75A	L610	1,828 (829) / 3,153 (1 430)	120 (3 040) / 120 (3 040)	TBD / TBD
FARMALL UTILITY C SERIES				
FARMALL 65C FARMALL 75C	L565 L620	1,940 (880) / 2,734 (1 240) 2,478 (1 124) / 3,179 (1 442)	105 (2 670) / 105 (2 670) 114 (2 910) / 114 (2 910)	3,241 (1 470) / 3,527 (1 600) 3,739 (1 696) / 4,665 (2 116)
FARMALL 90C FARMALL 100C FARMALL 110C FARMALL 120C	L103 L575 L620 L630	2,205 (1 000) / 3,241 (1 470) 2,028 (920) / 3,175 (1 440) 2,478 (1 124) / 3,179 (1 442) 2,632 (1 194) / 3,428 (1 555)	129 (3 270) / 129 (3 270) 125 (3 180) / 125 (3 180) 114 (2 910) / 114 (2 910) 123 (3 131) / 124 (3 149)	3,175 (1 440) / 3,417 (1 550) 3,351 (1 520) / 3,461 (1 570) 3,739 (1 696) / 4,665 (2 116) 4,455 (2 020) / 5,661 (2 567)
FARMALL UTILITY U SERIES				
FARMALL 110U FARMALL 120U	L103	2,359 (1 070) / 3,461 (1 570)	132 (3 350) / 132 (3 350)	3,395 (1 540) / 3,660 (1 660)
FARMALL 100A SERIES				
FARMALL 110A FARMALL 120A FARMALL 130A FARMALL 140A	L103* L104	2,094 (950) / N/A 2,557 (1 160) / 3,814 (1 730)	133 (3370) / NA 139 (3 530) / 139 (3 530)	3,020 (1 370) / N/A 3,682 (1 670) / 3,968 (1 800)
MAXXUM® SERIES				
MAXXUM 115 MAXXUM 125 MAXXUM 135 MAXXUM 145 MAXXUM 150	L103* L105 L105 Long Reach	2,381 (1 080) / N/A 2,932 (1 330) / 5,203 (2 360) N/A / 4,365 (1 980)	131 (3 330) / N/A 150 (3 810) / 150 (3 810) N/A / 156 (3 950)	3,439 (1 560) / N/A 4,674 (2 120) / 5,975 (2 710) N/A / 4,894 (2 220)
PUMA® SERIES				
PUMA 150 PUMA 165	L106 L106 Long Reach	3,594 (1 630) / 5,578 (2 530) N/A / 4,475 (2 030)	154 (3 920) / 154 (3 920) N/A / 166 (4 220)	5,137 (2 330) / 6,415 (2 910) N/A / 5,269 (2 390)
PUMA 185 PUMA 200 PUMA 220 PUMA 240	L107 L107 Long Reach	N/A / 5,622 (2 550) N/A / 4,519 (2 050)	N/A / 168 (4 270) N/A / 174 (4 430)	N/A / 6,768 (3 070) N/A / 5,490 (2 490)
MAGNUM™ SERIES				
MAGNUM 180 MAGNUM 200 MAGNUM 220 MAGNUM 240	L108	N/A / 6,151 (2 790)	N/A / 162 (4 110)	N/A / 8,620 (3 910)
MAGNUM 250 MAGNUM 280 MAGNUM 310 MAGNUM 340 MAGNUM 380	L795	N/A / 6,504 (2 950)	N/A / 183 (4 640)	N/A / 8,554 (3 880)

NSL – Non Self-leveling MSL – Mechanical Self-leveling * Compatible with 2WD only. [†]19.7 in (500mm) Forward of Pivot Pin
Per ASABE (American Society of Agricultural and Biological Engineers) specifications.

SAFETY NEVER HURTS!™ Always read the Operators Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

CIH19020701 02/2019

©2019 CNH Industrial America LLC. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates.